

w-series I-BAR SEALERS

i-bar sealers

W-350I
W-500I
W-650I
W-750I
W-900I




*Heat gun & film are sold separately

W-Series Bar Sealers are ivory in color and are available in 14", 20", 26", 30", and 35" with a round heating element for cut and seal. An optional 2.7mm heating element is available. The sealer is equipped with a film roller, film separator, heat gun holder, and a power outlet. The entire unit is steel constructed (including the work base) for quality and durability. The manufacturer's replacement kit comes with 3 round elements.

Easy to Operate: Turn on the power source. Set the timer to the lowest setting that will cut through the shrink film. Make sure that one layer of film is under the film separator & one layer of film is over the film separator. Pull enough of the CF shrink film to the sealing surface; seal & cut the start of your new roll of shrink film. Now pull enough of your film past the sealing bar to accommodate the item to be packaged. Insert the item between the 2 layers of centerfold shrink film & press down the sealing bar. As soon as you are able to pull your item away from the seal bar, the seal & cut is complete. Now turn your product a quarter of a turn so that your other unsealed edge can be sealed. Bring down the sealing bar as soon as you are able to pull away your item from the sealing bar, the seal is complete. Apply hot air to the shrink-packaged item using a heat gun to shrink the film uniformly.

i-bar sealers with cutters

W-350IC
W-500IC
W-650IC
W-750IC
W-900IC



*Heat gun & film are sold separately.

W-Series Bar Sealers with Cutters are exactly like the W-Series Bar Sealers except the heating element is a flat 2.7mm and there is a cutter unit attached on the right side of the sealing bar. The blade cuts 0.6" from the seal. The sealers are available in 14", 20", 26", 30", and 35" with a cutting length of 13", 19", 24 1/2", 28 3/4", and 34 1/2" respectively. The manufacturer's replacement kit includes 3 flat heating elements and 1 blade. An optional round heating element for cut and seal is available.

Easy to operate when using poly or shrink tubing: Turn on the power source. Set the timer to the lowest setting that will seal the material. If using poly or shrink tubing only, you can remove the film separator, which is used for centerfold shrink film. Pull enough poly tubing past the sealing bar to accommodate your product. Press down on the sealing bar until the timer light goes off and slide the cutter across the poly material while still holding down the sealing bar. Insert your product into the bag. Turn your bag around 180° so that you can now seal the open end and if needed, slide the cutter across the bag to remove any excess tubing.

Easy to operate when using CF shrink film: Turn on the power source. Set the timer to the lowest setting that will cut through the shrink film. Make sure that one layer of film is under the film separator & one layer of film is over the film separator. Pull enough of the CF shrink film to the sealing surface; seal & cut the start of your new roll of shrink film. Now pull enough of your film past the sealing bar to accommodate the item that is to be packaged. Insert the item between the 2 layers of centerfold shrink film and press down on the sealing bar. As soon as you are able to pull your item away from the seal bar, the cut & seal is complete. Now turn your product a quarter of a turn so that your other unsealed edge can be sealed. Bring down the sealing bar. As soon as you are able to pull away your item from sealing bar, the seal is complete. Using a heat gun, apply hot air to the shrink-packaged item to shrink the film uniformly.

Specifications

	W-350I/ W350IC	W-500I/ W-500IC	W-650I/ W-650IC	W-750I/ W-750IC	W-900I/ W-900IC
Power Supply	110V	110V	110V	110V	110V
Power (watts)	450	600	800	1000	1200
Weight (lbs.)	38	44	50	51	65
Sealing Length	14"	20"	26"	30"	36"
Cutting Length	13"	19"	24 1/2"	28 3/4"	34 1/2"
Dimensions (W x L x D)	23.5" x 16" x 5.5"	29.5" x 16" x 5.5"	35" x 16" x 5.5"	37.5" x 16" x 5.5"	45" x 16" x 5.5"
Distance from Center of Film to Seal	10.5"	10.5"	10.5"	10.5"	10.5"